

Parallel Numerics

Exercise 2: Numerical Integration & P2P Communication I

1 Numerical Integration




Figure 1: Subdivision of $[a, b]$ into $\#proc$ subintervals and subdivision of $[a_k, b_k]$ into n subsubintervals.

We are to calculate the definite integral of a function $f(x)$ in an interval $[a, b]$ using the trapezoidal rule. Before, we split up the overall interval $[a, b]$ into $\#proc$ equidistant subintervals $[a_k, b_k]$, $k \in \{0, 1, \dots, \#proc - 1\}$. $\#proc$ is the number of nodes available on a parallel computer. Afterwards, we divide the interval $[a_k, b_k]$ into n intervals with length $h = \frac{b_k - a_k}{n}$ and approximate the integral by a sum of trapezoids:

$$\begin{aligned}
 \int_{a_k}^{b_k} f(x) dx &\approx \sum_{i=1}^n \frac{h}{2} (f(a_k + (i-1)h) + f(a_k + ih)) \\
 &= \frac{h}{2} (f(a_k) + f(b_k)) + h \cdot \sum_{i=1}^{n-1} f(a_k + ih)
 \end{aligned} \tag{1}$$

- a) Implement the algorithm using the MPI send and receive operations.
- b) Test the application for $f(x) = -3x^2 + 3$, $[a, b] = [-1, 1]$, $n = 2, 4, 8$, and different numbers of processors.
- c) Test the application for $f(x) = x \sin(10x)$, $[a, b] = [0, 2\pi]$, $n = 2, 4, 8$ and different numbers of processors. Compute the analytical solution and compare it to the numerical




Figure 2: $f(x) = x \sin(10x)$.

one. What do you observe and why?

- d) Implement the following strategy for determining n on a node:

```

n = 1
Compute  $F_{numerical}^{(n)}$  (see formula (1))
do {
    n++
    Compute  $F_{numerical}^{(n)}$  (see formula (1))
} while (  $F_{numerical}^{(n)} - F_{numerical}^{(n-1)} \geq \varepsilon$  )

```

Test the algorithm for

$$f(x) = \begin{cases} 0 & \text{for } x \leq \frac{1}{2} \\ 1 & \text{for } x > \frac{1}{2} \end{cases}, \quad (2)$$

$[a, b] = [0, 1]$, $n = 2, 3, 4$ and different values for ε . Try to find out, how many iterations per node are performed. Is there a bottleneck?

- e) Before the application terminates, each node sends its contribution to the numerical result to node 0. You have used MPI send and receive to implement this behaviour. Is there a technical term for such a communication scheme?

2 P2P Communication I: MPI_Send and MPI_Recv

- a) Write an operation sequence that receives four integers from arbitrary senders (use the constant `MPI_ANY_SOURCE` as source number for the `MPI_Recv` operation) using the message tag 0 for each of them. Store the results in four integers `b0`, `b1`, `b2`, and `b3`.
- b) Consider the following code snippet

```
1     int a = 0;
2     MPI_Send(&a, 1, MPI_INT, 2, 0, MPI_COMM_WORLD);
3     a = 1;
4     MPI_Send(&a, 1, MPI_INT, 2, 0, MPI_COMM_WORLD);
```

running on node 0, and

```
1     int a = 2;
2     MPI_Send(&a, 1, MPI_INT, 2, 0, MPI_COMM_WORLD);
3     a = 3;
4     MPI_Send(&a, 1, MPI_INT, 2, 0, MPI_COMM_WORLD);
```

running on node 1.

What are possible values for `b0`, `b1`, `b2`, and `b3` when executing the four `MPI_Recv` operations from a) on node 2? Is there a unique solution? Are messages allowed to overtake?

- c) Define the term *blocking* for MPI commands.
- d) Define the term *not synchronized* for MPI commands.

3 Predefined MPI datatypes

For every MPI send or receive command, one has to specify a datatype. Make yourself familiar with the datatypes offered by the MPI interface. To what C datatypes do they correspond?